## 







**FLASH 400** is an IP rated audience blinder with 4 x 100 watts Warm white COB LEDS. Each one of the 4 zones can be controlled separately creating a dynamic pixel mapping chase effect. It delivers a bright powerful output and features an electronic strobe and smooth dimming to mimic the traditional blinders. It is housed in rugged aluminum cover making it perfect for all outdoor concert, stage, dance and event applications.

| SOURCE            | Light source: 4 x 100 watts LEDs<br>Color temperature: 3200k<br>LED life expectancy: 50,000 Hrs.                                                      |     | <b>Dimensions</b>            |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|-----|------------------------------|
| OPTICAL<br>SYSTEM | Beam angle: 50°                                                                                                                                       | 370 |                              |
|                   | Dimmer: Linear adjustment<br>Electronic strobe<br>4 zones control<br>Built-in dynamic effects                                                         |     |                              |
|                   | Control protocols: DMX, Sound, Master-Slave , Auto Run<br>Control channels: 4, 8 CHs                                                                  |     |                              |
| ELECTRICAL        | Input voltage: AC90-240V50/60HZ<br>Power consumption: 400 watts                                                                                       |     | $\bigcirc \bigcirc \bigcirc$ |
| CONNECTIONS       | DMX connections: IP DMX In/Out cables with 3 pin screw<br>lock connectors<br>Power connections: IP power In/Out cable, 3 pin screw lock<br>connectors |     | 210                          |
| PHYSICAL          | Dimensions: 370 x 370 x 120mm<br>Net weight: 11 Kg<br>Color: Black<br>Housing: Aluminum<br>IP rating: 65                                              |     |                              |