

Sleeve Block FD/HD44, XD, ST, FT50, XTS, TT, TTU, TTS

Sleeve blocks for TD44 Tower

| Productcode | For attachment |
|-------------|----------------|
| FD44-SB3 | 3x FD/HD44 |
| FD44-SB3-XD | 3x XD |
| FD44-SB3-ST | 3x ST |
| FD44-SB3-FT | 3x FT50 |
| SI-SB44-TT | TT |
| TD44-SB-TTU | TTU |
| TD44-SB-TTS | TTS |

TOP44-1
Universal Top Part for Motors for 1 Ton Chain Hoists


CS1-HS L/R
Hinge Set

STAB-44-117/150
Stabilizer bar for use with TD44-075 or 150 cm L=85 cm.

BASE-02 with OUTR-L02
Steel base on wheels with long outrigger

TD44 Tower

The TD44 Tower makes for an excellent vertical truss that allows the safe, quick lifting of regularly loaded horizontal HD/FD44, FT, XT and TT Truss Rig and Roofs to their service height. In terms of static, the TD44 Tower is designed for a high flexural- and pressure strain. Especially due to a roof this high, flexural strain is required.



Facts

- Steel base equipped with high quality cast wheels
- Build for extreme heights and loads
- Up to 16 meters (52ft.)
- Multifunctional Top Part for use with manual and motorized hoists

Specifications TD44 Tower

Max. Height: 16 m. (52 ft.)
 Max Loading: 2000 kg. (4400 lbs)
 Tower Truss: TD44
 Sleeve Block: TTU, TTS, TT, XTS, FT50, ST, XD, FD/HD44

Top section & Sleeve Blocks

A new multifunctional top part for use of manual chain hoist as well as motorized hoist has been redesigned and built stronger.

Standard sized XTS and TT corner blocks with usage of 2 bolted sleeve plates guarantees a perfect geometric rig. These blocks make it possible to fit the TT / XTS / FT50 Truss to all four sides mby using bolted receivers. The upper sleeve plate is equipped with an integrated hanging point. The standard FD44 sleeve blocks have predesined welded receivers on 3 sides for attachments of XD/ST or FT50 truss.

Hinge set

A strong, safe and cost effective solution to erect the TD44 Tower. The hinge sets are 100mm long. Those half connectors with a hinge fork allow a very high vertical load. 4 Hinge sets (2 left and 2 right) are required per tower.

Base section & Outriggers

Steel Base on wheels available with short outriggers and long outriggers in combination with stabilizer bars.

Ballast Safe

Product Code BS-44

The Ballast-Safe is a full integrated base in a stage and gives the benefit of reducing the total required ballast by taking the self weight of the stage structure. The support beams of the Ballast-Safe are equipped with steel wedge heads to attach the guy wires. The Ballast allows you to set your towers and roof up on a flat, levelled platform which saves you a ton of build up time.

Ballast Base

Product Code BL-44

This is an alternative base frame which is an engineered steel flexible frame to the base to put ballast on. Solid wheels enables you to transport the ballast easily and sufficient spindles lock down the frame. Standard pallet sized ballast fit on the base frame to ensure you the correct positioning of the ballast.

Erecting System

Product Code TES-44

This easy and fast tower frame, strapped with ratches to the main truss, can be used to erect the towers with just the help of an electrical chain hoist.