

XLR Cable - 3 Pin with SCSM3/SCSF3 for Audio, Microphone



MIC-M1 Professional Microphone Cable 0.22 mm² AWG 24

Conductor

| | |
|--------------|--------------------------|
| Quantity | 2 |
| Construction | 02/10mm |
| Resistance | 8.90 Ω/km (Max. at 20°C) |

Jacket

| | |
|-----------|-----------|
| Material | PVC |
| Diameter | 6.0±0.30 |
| Thickness | 1.45±0.20 |
| Colour | Black |

Insulation

| | |
|-----------|------------|
| Material | PE |
| Diameter | 1.4±0.10mm |
| Thickness | 0.4±0.10mm |
| Colour | Red, White |

Jacket

| | |
|---------------------|--------------|
| Capacitance at 1kHz | 98pF/m |
| Voltage Breakdown | 125V/15sec |
| Flex Life | 20000 cycles |
| Tensile Strength | 500N |
| Working Temp. | -20°C~ 70°C |



Seetronic SCSM3 3 pin XLR male cable connector

Product Features

- 3-core XLR male cable connector with nickel plated shell and silver plated contacts
- The metal shell adopts external thread design which is convenient for quick locking with the boot and reducing assembly time
- Two cable clamps are provided for different cable diameters; black clamp 3.5-6mm; white clamp 6-8mm
- Noring design, more compact
- Colored boots available for coding and identification
- The boot is equipped with a polyurethane sealing sleeve to prevent the cable from being affected by bending pressure to the greatest extent



Seetronic SCSF3 3 pin XLR female cable connector

Product Features

- 3-core XLR female cable connector with nickel plated shell and silver plated contacts
- The metal shell adopts external thread design which is convenient for quick locking with the boot and reducing assembly time
- Two cable clamps are provided for different cable diameters; black clamp 3.5-6mm; white clamp 6-8mm
- Noring design, more compact
- Colored boots available for coding and identification
- The boot is equipped with a polyurethane sealing sleeve to prevent the cable from being affected by bending pressure to the greatest extent

