



*With Optional Barndoor And Diffuser



CPX160 is an outdoor IP65 LED Bar powered by 16 x 10W RGBW LEDs with an improved optical system for high brightness and smooth color mixing. The CPX160 is built for multipurpose architectural and entertainment applications. It can deliver a bright static wash and a dynamic 8 zones pixel mapping effect.

SOURCE Light source: 16 x 10 watts, 4 in 1 RGBW LEDs
LED life expectancy: 50,000 Hrs.

OPTICAL SYSTEM Beam angle: 20°
Optional 15° Frost Filter (FF15-CPX160)
Optional Single Barndoor (BD-CPX160)

DYNAMIC EFFECTS Dimmer: 4 selectable dimming curves
Color mixing: RGBW
Strobe and fade effect
Built-in color and dynamic macros

CONTROL & PROGRAMMING Control protocols: DMX, RDM, Auto Run
Display : TFT displayer with 4 buttons
Control channels: 3, 8, 12, 32, 37 CHs

ELECTRICAL Input voltage: AC100-240V/50-60Hz
Power consumption: 180 watts

CONNECTIONS DMX connections: IP65 Seetronic 3 pin XLR In/Out
Power connections: IP65 Seetronic PowerCon In/Out

PHYSICAL Dimensions: 1000 x 90 x 113 mm
Net weight: 5.5 Kg
Color: Black
Housing: Aluminum
Anti UV and Salt coat painting
IP rating: 65
Operating temperature: -20°C/45°C

Dimensions

